

METEOR MAXIMA



HIGH RESISTANCE, ANTI-SLIP, SUPER SHINY ACRYLIC EMULSION

- Anti-slip effect tested by UL laboratories
- Very high level shine with less frequent maintenance
- Suitable for spray cleaning and spray buffing systems with anti-yellowing effect



Emulsion formulated with acrylic and polyurethane polymers to guarantee maximum shine and tread resistance. Anti-yellowing formula. Resistant to washing with disinfectants, even alcohol based, if used correctly and with the correct dilution. Registered with Underwriters Laboratories Inc. as anti-slip, high resistance wax.

HOW TO USE

After carefully removing wax using a wax stripper from the SUTTER PROFESSIONAL range, apply two coats of wax using the special wax applicator. Leave to dry approximately 30 - 60 min. between one coat and the next. Also suitable for UHS spray cleaning or spray buffing maintenance. Recommended maintenance: AZZURRO UL for wet maintenance; RAPID UHS UL for spray method.



METEOR MAXIMA

 DILUTION

Ready to use.

FEATURES

Product yields (m²/lt):

Operation category	Conc.%	Product yield (m ² /lt)	Notes
FLOOR WAXING	100%	20	2 coats

Volume (lt) of pure product diluted according to suggested dilutions.

 TECHNICAL DATA

ASPECT: Opaque liquid

COLOR: Creamy white

PERFUME: Technical

COV: 0,00%

PH	Active substance [%]	Density (g/ml)	Pressure (bar)	Viscosity (cP)	Total dry residue [%]
8,2 ± 0,5		1.009			25 ± 1

 WARNINGS

May cause an allergic skin reaction. Harmful to aquatic life with long lasting effects. Avoid breathing vapours. Wear protective gloves and eye/face protection. If skin irritation or rash occurs: Get medical advice/attention. Take off contaminated clothing and wash it before reuse. Contains METHYLCHLOROISOTHIAZOLINONE, METHYLISOTHIAZOLINONE. May produce an allergic reaction. Contains ZINC AMMONIA CARBONATE COMPLEX.



WARNING

METEOR MAXIMA

NOTES

Do not apply METEOR MAXIMA at temperatures below 10° C. Keep away from freezing. Some floors may be difficult to penetrate and/or anchor the treatment. Check adherence in a small area of the floor before applying the product.

Before use, please always refer to the Technical Data Sheet and the Safety Data Sheet, with the exposure scenario, of the product. Use the PPE specified in the Safety Data Sheet.

Sutter Professional cannot be considered liable for any damages due to improper product use.

Only for professional use. Safety data sheet available on request.

PACKAGING

Code	Size	Quantity	Pallet
5352	Kg 5	4	9x4=36